







The Model 122 fits four COMO Filters, giving it the filtration capacity needed for large reservoirs while maintaining 1  $\mu$ m particle and 20 ppm water performance. Each COMO Filter holds up to 20 pounds of dirt and 1 gallon of water, so you can extend fluid life and reduce downtime with fewer filter changes than the competition.

## THIS PRODUCT FILTERS

- Hydraulic oil
- Gear oil
- Lube oil
- Turbine oil

Transformer oil

- Engine oil
- Vacuum pump oil
- Fire-resistant hydraulic oil
- Many other industrial fluids

## SPECIFICATIONS

- · Two C-1002 chrome-plated depth-filter housings
- 7, 11, or 15 GPM iron gear pump with Buna-N mechanical seals
- 3/4 or 1 HP, 115 V, single-phase, 60 Hz, 1725 RPM, TEFC Motor
- · Portable, chrome-plated frame with oil-resistant wheels
- Dimensions: 23" W x 24" D x 60" H
- · Approximate weight: 230 lbs.

## STANDARD FEATURES

- · Pressure switch with high/low shut-off for unattended operation
- · Fluid transfer feature to bypass depth-filter housings
- · Gate valve for flow control
- · Motor starter with thermal overload protection
- · Power and pump indicator lights
- Pressure gauge to monitor filter element life
- · Inlet wye strainer to protect pump

Don't let particulate & water contamination affect production.

Reduce downtime and maximize productivity by using the COMO Model 122.