



Dedicated Filtration System Model 165



The Model 165 is designed for kidney-loop filtration of a single machine. With dozens of filter options, you can meet your exact cleanliness goals—as low as 1 µm and 20 ppm water. Each COMO Filter holds up to 20 pounds of dirt and 1 gallon of water, so you can extend fluid life and reduce downtime with fewer filter changes than the competition.

- THIS PRODUCT FILTERS**
- Hydraulic oil
 - Engine oil
 - Gear oil
 - Vacuum pump oil
 - Lube oil
 - Fire-resistant hydraulic oil
 - Turbine oil
 - Many other industrial fluids
 - Transformer oil

SPECIFICATIONS

- One C-1000 chrome-plated depth-filter housing
- 1 or 3 GPM iron gear pump with Buna-N mechanical seals
- 3/4 HP, 115 V, single-phase, 60 Hz, 1725 RPM, TEFC motor
- Freestanding, powder-coated frame
- Dimensions: 18" W x 20" D x 44" H
- Approximate weight: 130 lbs.

STANDARD FEATURES

- Toggle switch motor starter
- Pressure gauge to monitor filter element life
- Frame with bolt holes for floor mounting capability
- Inlet wye strainer to protect pump
- Internal pressure relief in pump
- Stainless-steel element lifter

**Don't let downtime cut into your profits.
Extend fluid life and improve machine reliability with a COMO Model 165.**